Specifications of Prime Mover Model 4-3860

		4-3860		
	Make / Model			Millat/Perkins 4.236
	Type / Configuration			Diesel / 4 cycle Vertical
Щ	No. of Cylinders			4 In-line
	Bore / Stroke			98.4 / 127
	Capacity			3.86 (236.2)
	Output at:	2250 rpm	kw/bhp	
	(Rating Standard 1 BS AU 141a:1971)	2200 rpm	kw/bhp	55.9 / 75
ENGINE		2000 rpm	kw/bhp	52.7 / 70.5
ш		1800 rpm	kw/bhp	48.8 / 65.5
		1500 rpm	kw/bhp	41.7 / 56
	Combustion System / Aspiration			Direct / Natural
	Cooling System			Water Cooled with tropical radiator capable to operate in Amb. Temp. 50° C
	Power take-off			From Fly wheel End
	Direction of rotation			Clockwise - Viewed from front
TIES	Engine		liters	7.5
CAPACITIES	Coolant Radiator		liters	12.2
Ö	Fuel Tank		liters	45
	Clutching / Declutching with lever			
	12V Alternator			
Ę	Instrumentation:			
JME	Panel mounted on base frame complete with:			
ing	(a) Tacho meter			
STANDARD EQUIPMENT	(b) Hour meter			
	(c) Ammeter			
	(d) Low Oil Pressure Gauge			
	(e) Water Temperature Gauge			
	(f) Battery Charging			
	(g) Ignition Key Switch			
S	Ov erall Length		mm (in)	2100 (83)
oisi	Overall Width		mm (in)	1140 (45)
DIMENSIONS	Overall Height (w/o Silencer)		mm (in)	1640 (65)
	Net Weight		kg	750